



CL03 SERIES

THE VALVE SYSTEM WITH THE HIGHEST PROTECTION CLASS

It's that easy





Specialists in Valves, Controls, Pneumatics and Fluid Measurement



An O'Keefe Controls Company

CL03 series valve system





The ultimate in hygienic design

Clean line to the maximum. The CL03 series is the ideal valve system for pneumatic solutions in the food industry – hygienic design, utmost configuration flexibility, module extension possible at any time, and protected at the highest level.

Flexibility and safety without compromises

Through its hygienic design and the use of NSFH1 lubricants, the CL03 is suitable for use in applications with direct food contact. The system features an especially high protection class of IP69K and the special resistance of the high-tech polymer to aggressive chemicals and cleaning materials enable simple and fast cleaning of the equipment at any time, making it ideal for wash-down applications, even under harsh conditions and high temperatures. Simply unbeatable.

- Modular, flexible, hygienic
- Also available as CL03-EV single valve
- Two sizes can be combined



Variants	CL03	CL03-XL	CL03-EV
Max. flow	850 l/min	1100 l/min	700 l/min
Valve functions	2x3/2, 5/2, 5/3 directional valve		
Connections	G1/4, Ø 5/16, Ø 10, Ø 3/8		Ø 8, G1/8
Electrical control	Multipole plug, fieldbus		M12x1
Protection class	IP66K, IP67, IP69K		IP65, IP67, IP69K
Valve positions/ solenoid coils	16/32	18/32	1/2
Food-grade grease	~	•	•

The first choice for hygienic design, with added flexibility

Two combinable sizes, alternative electrical connections, and the ability to additionally integrate single valves from the series into an installation make the series ideal for custom-configured pneumatics solutions. Based on its hygienic design, CL03 systems can also be placed directly in the vicinity of the actuators, cutting down on control cabinets as well as additional tubing and cables for power and compressed air supply.

- No joints or gaps, easy to clean
- High safety through IP69K protection class
- Ideal for (high pressure) wash-down applications
- Food-grade grease
- Flexible for custom configurations
- ✓ Up to 32 pressure levels
- First EHEDG certified pneumatics valve system.